

BEST AVAILABLE COPY

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-291162

(43)Date of publication of application : 26.10.1999

(51)Int.Cl.

B24B 37/04

H01L 21/304

H01L 21/304

(21)Application number : 10-099231



(71)Applicant : NEC CORP

(22)Date of filing : 10.04.1998

(72)Inventor : MASUDA YOKO
UTO MITSUYOSHI**(54) POLISHING DEVICE****(57)Abstract:**

PROBLEM TO BE SOLVED: To restrain the occurrence of polishing quantity abnormality in a substrate outer peripheral part by arranging the ring-shaped resin part formed on the surface contacting with a polishing pad of a retainer ring and a ring-shaped holding member composed of a material being fixedly arranged on the resin part and having mechanical strength higher than the resin part.

SOLUTION: A retainer ring 101 is formed as a two-piece structure of the resin part 101a and the metallic part 101b, so that the retainer ring 101 is remarkably improved in mechanical strength. While, in the retainer ring 101, the resin part 101a only contacts with a polishing pad 102, but the metallic part 101b does not contact with it. Therefore, a metallic component expands to the polishing pad 102, adverse influence is not exerted on a characteristic of a device formed on a substrate 105, and even if a polishing processing quantity increases, polishing abnormality caused in the substrate outer peripheral part of a polishing object can be restrained.

**LEGAL STATUS**

[Date of request for examination] 10.04.1998

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 2917992

[Date of registration] 23.04.1999

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office